

# NEVER-SEEZ®

Anti-Seize & Lubricating Compound

PRODUCT DATA

## Pipe Compound with Teflon®

### Product Description

Bostik Never-Seez Pipe Compound is a superior lubricating and anti-seize compound formulated to provide maximum thread lubrication in a wide range of pipe threads and fittings. The use of Teflon® and other solid lubricant additives in Never-Seez Pipe Compound allows greater thread engagement which enhances sealing. Never-Seez Pipe Compound prevents corrosion and galling of threads for easy disassembly. Recommended for use on black iron, galvanized stainless steel, and high pressure steam pipes in contact with cast iron, malleable, brass, stainless steel and galvanized fittings.

### Product Benefits

- Prevents corrosion, galling and seizing.
- Assures easy disassembly.
- Suitable for water, natural gas, air, steam and hydraulic oils.
- Suitable for all combinations of pipe and fittings.
- Non-toxic and non-hazardous.

### Product Applications

- Water lines, non-potable.
- Steam pipe fittings.
- Hydraulic lines and fittings.
- Pneumatic systems.
- Natural gas lines.

### Limitations

- Do not use on oxygen systems.
- For temperatures above 350° F use Never-Seez Regular or Pure Nickel Special.

### Other Anti-Seize Lubricants from Bostik

- Regular Grade
- Regular Grade, Nuclear Certified
- Regular Grade LV
- Pure Nickel Special
- Nuclear Grade, Nickel Special
- Nuclear Grade Non-Aluminum, Nickel Special
- High Temp Stainless
- High Temp Stainless, Nuclear Certified
- Blue Moly
- Black Moly
- Red Bearing Lubricant
- WhiteFood Grade with PTFE
- High Temperature Bearing Lubricant
- Marine Grade



### Technical Specifications

Color	Off White	
Temperature Range	10°F to <del>325</del> 525°F	
Water Resistance	Excellent	
Particle Size	2 mil. maximum	
Specific Gravity	1.15	
Coefficient of Friction "K" Factor	0.16	
		ASTM Test Method
Flash Point	500°F	D-92
Dropping Point	388°F	D-566
Copper corrosion test (212°F, 24 hours)	No corrosion	D-130-83

**CENTROSA**

**Ingredients:** Contains a special, high-quality grease with Teflon®, mica, and zinc oxide.

**Shelf Life:** NEVER-SEEZ Pipe Compound does not deteriorate with age when stored unopened at temperatures below 120°F. Quality and performance are guaranteed for five years after purchase on unopened containers.

**Use in accordance with Material Safety Data Sheet.**

### Ordering Information

#### PIPE COMPOUND

STOCK NUMBER	DESCRIPTION	SIZE
NP-160	Flat Top Can	1 lb.
NPBT-4	Brush Top Can	4 oz.
NPBT-8	Brush Top Can	8 oz.
NPBT-16	Brush Top Can	1 lb.

#### IMPORTANT NOTICE:

All statements, technical information and recommendations set forth herein are based on tests which Bostik believes to be reliable. However, Bostik does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sales of this product shall be on terms and conditions set for the on Bostik's order acknowledgment. Bostik warrants that the product conforms with Bostik written specifications, and is free from defects. BOSTIK DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK BE LIABLE FOR DIRECT, CONSEQUENTIAL ECONOMIC OR OTHER DAMAGES.

**Bostik**

BOSTON STREET  
MIDDLETON, MA 01949  
TEL. 508-777-0100  
FAX 508-750-7212

8/94 - N11C - 10M

106198 KO